

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 386 595 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
04.02.2004 Bulletin 2004/06

(51) Int Cl.7: **A61H 1/00, A61H 15/00,
A61H 37/00**

(21) Application number: **02017311.8**

(22) Date of filing: **01.08.2002**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Marcantoni, Egidio**
61100 Pesaro (IT)

(74) Representative: **Tetzner, Michael, Dipl.-Ing. et al**
Van-Gogh-Strasse 3
81479 München (DE)

(71) Applicant: **CIAR S.P.A.**
61020 Pesaro (IT)

(54) **Massage device**

(57) Massage device for an item of furniture for sitting and/or lying on, having a first shaft and a second shaft which are supported parallel with one another in a frame, and having at least one arm which carries at least one massage body, the arm being coupled to the two shafts in such a manner that a rotation of the shafts brings about a massage movement of the massage body in a first and/or second direction. Means are also provided for displacing the massage body relative to the frame and they are formed by means for changing the distance between the two shafts.




Fig. 1

EP 1 386 595 A1

Description

[0001] The invention relates to a massage device for an item of furniture for sitting or lying on, having a first shaft and a second shaft which are supported parallel with one another in a frame, and at least one arm which carries at least one massage body. The arm is coupled to the two shafts in such a manner that a rotation of the shafts brings about a massage movement of the massage body in a first and/or second direction.

[0002] Such massage devices are installed, for example, in the backrest of an armchair. The frame is adjustable in guide rails in the vertical direction so that both the neck region of a user and also the lower back region can be massaged.

[0003] Massage armchairs are often used not only for massaging, but also, for example, for reading or watching television. Whereas pressure is to be exerted on the user's back during massage, it is desirable when reading or watching television if the massage body is not felt in the back.

[0004] It has therefore already been proposed to form the guide rails, in which the frame can be adjusted in the vertical direction, in such a manner that the massage body is moved away from the user's body at the end of the guide rails. In addition, it has already been proposed to adapt the guide rails to a user's spinal column in the other regions also, in order to exert a correspondingly adapted pressure of the massage body in various regions of a user's back.

[0005] EP-A-1 048 281 also discloses a massage device in which the massage body, in addition to the usual kneading or tapping massage, can also be adjusted perpendicularly to the frame. Thus, the massage body can be moved into a resting position in which it no longer exerts pressure on a user's back. This adjustment facility also enables the user to set the pressure of the massage body to his particular requirements. The known embodiment provides that the two shafts are supported together with the drive motors on a slide on the frame, it being possible to adjust the slide by means of a further motor. An adjustment of the slide then brings about a displacement of the two shafts and therefore of the massage bodies relative to the frame.

[0006] Although this known embodiment permits very versatile and individual settings, the mechanism requires a relatively large installation space, as a result of which the backrest has to be in a correspondingly thick form.

[0007] The object of the invention is therefore to provide a massage device according to the precharacterising clause of claim 1, in the case of which the means for displacing the massage body relative to the frame require a smaller installation space.

[0008] According to the invention, the object is achieved by the features of claim 1.

[0009] The massage device according to the invention for an item of furniture for sitting and/or lying on con-

sists substantially of a first shaft and a second shaft which are supported parallel with one another in a frame, and at least one arm which carries at least one massage body, the arm being coupled to the two shafts in such a manner that a rotation of the shafts brings about a massage movement of the massage body in a first and second direction. In addition, means are provided for displacing the massage body relative to the frame and they are formed by means for changing the distance between the two shafts.

[0010] Owing to the coupling of the arm carrying the massage body to the two shafts, the massage body can be displaced relative to the frame as a result of changing the distance between the shafts by displacing at least one of the two shafts.

[0011] Further forms of the invention are the subject-matter of the subsidiary claims.

[0012] According to a preferred embodiment, the arm carries the massage body at one end and is coupled to the first shaft by its other end. Furthermore, the arm is in operative contact with the second shaft in an intermediate region. The rotation of the one shaft brings about a movement of the massage body which takes place substantially parallel with the shaft, while the rotation of the other shaft brings about a movement of the massage body which takes place substantially perpendicularly to the shaft.

[0013] According to a special embodiment, the means for changing the distance between the two shafts have a motor for displacing one of the two shafts.

[0014] Further advantages and forms of the invention will be explained in more detail hereinafter with reference to the description of an embodiment and the drawings.

[0015] In the drawings:

Figure 1 is a perspective view of a massage device installed in a guide frame,

Figure 2 is a perspective view of the massage device from a first viewing angle,

Figure 3 is a perspective view of the massage device from a second viewing angle,

Figure 4 is a diagrammatic side view of the massage device in the resting position, and

Figure 5 is a diagrammatic side view of the massage device in a working position.

[0016] In the drawings, the massage device according to the invention is marked with the reference sign 1. It consists substantially of a first shaft 2 and a second shaft 3 which are supported parallel with one another in a frame. An arm 5 carries a massage body 6 at its one end and is coupled to the first shaft 2 by its other end. In a central region, the arm is also in operative contact

with the second shaft 3 by way of a linkage 7.

[0017] The first shaft 2 is driven by means of a first gear motor 8 and the second shaft 3 is driven by means of a second gear motor 9.

[0018] In the case of the embodiment shown in the Figures, the massage device has two arms 5, for the sake of clarity only one arm 5 being shown in Figures 2 and 3. The second arm would be in operative contact with the free ends of the shafts 2 and 3.

[0019] The type of coupling of the arm 5 to the shaft 2 or 3 determines the type of movement transmitted onto the massage body by the rotation of the shaft. In the embodiment shown, the ends of the shaft 2 are slightly angled relative to the shaft axis so that the rotation of the shaft 2 brings about a movement of the massage body which takes place substantially parallel with the shaft 2.

[0020] The coupling of the arm 5 to the second shaft 3 by way of the linkage 7 is effected by way of an eccentric portion 3a which, when the shaft 3 rotates, brings about a movement of the massage body which takes place substantially perpendicularly to the shaft 3.

[0021] The movement of the massage body caused by the shaft 3 is normally referred to as tapping massage while the movement based on the rotation of the first shaft 2 is referred to as stroking massage. In operation, the two massage movements can of course also be superposed on one another.

[0022] The linkage 7 is connected to the second shaft 3 by a ball-and-socket joint 10a 10b and also comprises two portions which are so connected to one another in the central region by an articulation 11 that they can be pivoted about an axis which extends substantially perpendicularly to the second shaft 3. This linkage on the one hand enables the tapping movement to be transmitted onto the massage body 6 perpendicularly to the shaft 3 and, on the other hand, permits the movement parallel with the shafts brought about by the first shaft 2.

[0023] For as compact an arrangement of the massage device as possible, it is especially advantageous if the two gear motors 8, 9 are connected to the two shafts in a central region thereof.

[0024] In the embodiment shown, the massage body 6 is formed by a carrier which is supported pivotably on the arm 5 and on which several massage rollers 6a - 6d are arranged. Instead of massage rollers, it is, however, also possible to use balls or other massage bodies.

[0025] Figure 1 shows the installation situation of the massage device 1 in a guide frame 12 which is arranged, for example, in the backrest of a massage chair. The guide frame 12 provides lateral rails 12a in which the frame 4 of the massage device can be moved up and down, for example by way of rollers 13. The movement of the massage device 1 in the guide frame 12 is effected by means of a spindle 15 driven by a motor 14.

[0026] By activating the motor 14, the massage device 1 can be moved up and down in the guide frame along the spindle 15. As that happens, the massage

bodies 6 exert pressure on the back of the person sitting in the massage chair. However, the person also feels the massage bodies when they are not in action. Since, however, this greatly impairs comfort, the massage device 1 described above provides means for bringing the massage body into a resting position in which the massage body does not exert pressure on a person's back.

[0027] Those means are explained in more detail hereinafter with reference to Figures 4 and 5.

[0028] According to the invention, it is provided that one of the two shafts 2,3 be supported displaceably on the frame 4 while the other shaft is fitted in a stationary manner. In the embodiment shown, the second shaft 3 is supported on the frame 4 in a stationary manner while the first shaft 2 is arranged to be displaceable. For that purpose, the first shaft 2 is mounted on a slide 16 which is moveable to and fro by a spindle driven by a motor 18 (double arrow 20).

[0029] In the embodiment shown, the displacement of the first shaft 2 takes place in the plane containing the two shafts 2,3.

[0030] In the resting position according to Figure 4, the shafts 2,3 are at a distance L0 from one another while the distance in a working position according to Figure 5 is shortened to L1. Owing to the fact that the arm 5 is articulated pivotably at its one end to the first shaft 2 and the arm is also coupled to the second shaft 3 by way of the linkage 7, a displacement of the first shaft 2 brings about a pivoting of the arm 5 relative to the frame 4. However, a pivoting of the arm 5 also brings about a displacement of the massage body 6 relative to the frame 4. Between the resting position according to Figure 4 and the working position according to Figure 5, the massage body 6 is displaced relative to the frame 4 by the amount H.

[0031] The motor 8 is coupled to the first shaft 2 and is therefore displaced as well. Of course, in addition to the resting position, not just one but any desired number of working positions is possible within the scope of the invention. For example, the motor 18 could be activated in a specific manner when the frame 4 is displaced in the guide frame 12. Thus, the massage body 6 can be specifically adapted to the shape of a user's spinal column. The pressure of the massage body could also be altered in specific positions of the frame 4.

[0032] Owing to the fact that the first shaft 2 with its associated motor 8 is displaced in the same plane in which the second shaft 3 with its associated motor 9 is arranged, an extremely compact structural unit is obtained which requires less installation space than the solutions known hitherto.

Claims

1. Massage device (1) for an item of furniture for sitting and/or lying on, having

- a. a first shaft (2) and a second shaft (3) which are supported parallel with one another in a frame (4),
- b. at least one arm (5) which carries at least one massage body (6),
- c. the arm being coupled to the two shafts in such a manner that a rotation of the shafts brings about a massage movement of the massage body in a first and/or second direction,
- d. and means for displacing the massage body relative to the frame,
characterised in that
- e. the means for displacing the massage body relative to the frame are formed by means (16, 18, 19) for changing the distance between the two shafts.
- ised in that** the two shafts (2,3) are driven independently of one another by means of a respective gear motor (8, 9).
2. Massage device according to claim 1, **characterised in that** the arm (5) carries the massage body (6) at one end and is coupled to the first shaft (2) at the other end.
 3. Massage device according to claim 1, **characterised in that** the arm (5) carries the massage body (6) at one end and is coupled to the first shaft (2) at the other end, and the arm is also in operative contact with the second shaft (3) in a central region.
 4. Massage device according to claim 1, **characterised in that** the rotation of the one shaft (2) brings about a movement of the massage body (6) which takes place substantially parallel with the shaft, while the rotation of the other shaft brings about a movement of the massage body which takes place substantially perpendicularly to the shaft.
 5. Massage device according to claim 1, **characterised in that** one of the two shafts (2, 3) is supported displaceably on the frame.
 6. Massage device according to claim 1, **characterised in that** the means for changing the distance between the two shafts comprise a motor (18) for displacing one of the two shafts.
 7. Massage device according to claim 1, **characterised in that** the arm (5) carries the massage body (6) at one end and is connected in an articulated manner to the first shaft (2) at the other end and, in an intermediate region, the arm (5) is also in operative contact with the second shaft (3) by way of a linkage (7).
 8. Massage device according to claim 1, **character-**





Fig. 1






Fig. 3




Fig. 4




Fig 5



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 01 7311

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	PATENT ABSTRACTS OF JAPAN vol. 016, no. 207 (C-0941), 18 May 1992 (1992-05-18) & JP 04 038905 A (FUJI IRIYOUKI:KK), 10 February 1992 (1992-02-10) * abstract *	1-8	A61H1/00 A61H15/00 A61H37/00
A	--- EP 0 832 634 A (SANYO ELECTRIC CO) 1 April 1998 (1998-04-01) * column 4, line 35 - column 7, line 12; figures 1-5 *	1-4,7,8	
A	--- DE 94 19 742 U (KUANG-YU METAL WORKING CO) 2 February 1995 (1995-02-02) * page 2, line 14 - page 5, line 31; figures 1,2 *	1-4,7,8	
A	--- US 6 083 181 A (MARCANTONI EGIDIO) 4 July 2000 (2000-07-04) * column 3, line 25 - column 5, line 40; figures 1-4 *	1-4,7,8	
E	--- DE 202 07 288 U (GRUEGER ULRIKE ;REIBER PETRA (DE)) 19 September 2002 (2002-09-19) * page 9 - page 18; figures 1,2,8,9 *	1-8	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A61H
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 10 February 2003	Examiner Oelschläger, H
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EP0 FORM 1503 03.92 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 02 01 7311

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office (EPO) file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-02-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 04038905	A	10-02-1992	NONE	
EP 0832634	A	01-04-1998	JP 10099392 A	21-04-1998
			JP 10099393 A	21-04-1998
			AT 222740 T	15-09-2002
			DE 69714928 D1	02-10-2002
			EP 0832634 A1	01-04-1998
			KR 256438 B1	15-05-2000
			US 6224563 B1	01-05-2001
DE 9419742	U	02-02-1995	DE 9419742 U1	02-02-1995
US 6083181	A	04-07-2000	IT M1960662 A1	06-10-1997
			IT M1961545 A1	23-01-1998
			DE 836464 T1	02-03-2000
			WO 9737627 A1	16-10-1997
			EP 0836464 A1	22-04-1998
			AT 203390 T	15-08-2001
			DE 29724469 U1	07-06-2001
			DE 69705791 D1	30-08-2001
			DE 69705791 T2	22-11-2001
			DK 836464 T3	22-10-2001
			ES 2160937 T3	16-11-2001
DE 20207288	U	19-09-2002	DE 20116001 U1	06-12-2001
			DE 20207288 U1	19-09-2002
			DE 20200216 U1	21-03-2002
			DE 20205116 U1	02-10-2002